



## LIFEGUARD CHASSIS SPECIFICATIONS POLARIS RANGER 6X6

### ENGINE

Engine Type	Twin Cylinder, 4 - Stroke
Displacement	760 cc, HO
Lubrication	Pressurized Wet Sump
Cooling System	Liquid - Cooled
Starting	Electric
Exhaust	Canister Style

### DIMENSIONS & CAPACITIES

Wheelbase	Approx. 105"
Length/Width/Height	168/63/76 in.
Ground Clearance	12 in.
Dry Vehicle Weight	2160 Lbs
Gross Vehicle Weight	4200 Lbs
Top Speed	50 MPH
Hitch Towing Capacity	2000 Lbs

### FUEL

Fuel System	EFI
Fuel Tank	9.0 gal/34.1 ltr
Fuel Delivery	Electronic Fuel Pump
Fuel Type	Gas 87 Octane or 89 Oxygenated

### ELECTRICAL

Alternator	500 Watts
Battery	12 Volt - 30 Amp
Headlight	50 w Quartz - Halogen
Brake Light/Tail Light	STD/STD
DC Outlet	Dash Receptacle

### DRIVETRAIN

Transmission	Auto- PVT Variable Transmission H,L,N,R
Drive System	On-Demand True 6 WD/Mid Diff. Lock
Final Drive	Shaft

### STEERING & SUSPENSION

Power Steering	Polaris Model Electronic Controlled
Front Suspension	Dual A-Arm w 9.6 in. Travel
Rear Suspension	4-Wheel Dual A-Arm, IRS 9 in. Travel

### BRAKES & TIRES

Brakes - Front/Rear	Hydraulic Disc w/ Dual -Bore Front Calipers
Parking Brake	Hand - Actuated, Dash Mounted Lever
Front Tire Size	25x10x12 Off-Road Tire on Painted Steel Rims
Rear Tire Size	25x11x12 Off-Road Tire on Painted Steel Rims



For more information, visit us at [www.nassaufire.com](http://www.nassaufire.com),  
email us at [salesadmin@nassaufire.com](mailto:salesadmin@nassaufire.com)  
or call us at 877-538-8220

Rev 9/08/10